

Gigalink RR-GQ1621A 16 Port PoE Switch



- ✧ 16*10/100Mbps POE port, 2*100/1000Mbps, 1SFP*100/1000Mbps UP Link port,
- ✧ 250m Distance
- ✧ Support IEEE802.3AF/AT
- ✧ Whole Power: 250W (52V 4.8A)
- ✧ All ports supported by MDI/MDIX auto flip and self negotiation
- ✧ Supply 16 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- ✧ Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- ✧ Each port max. power supply reached 30W.

Application:

- ✧ Wireless Access Point
- ✧ IP Camera
- ✧ IP Phone
- ✧ Computer Networks

Specifications:

Product	16 Port POE Switch
Model	RR-GQ1621A
POE Port	1 to 16 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤250W (52V 4.8A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	12.8Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100BASE-tx: 14800pps/port 1000BASE-tx: 148000pps/port
MAC Address	MAC address table 16K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10°-- 55°C
Weight	2.8kg
Size	295×180×45(L*W*H)mm